



KLED RANGE

MAIN FEATURES

- Multi-voltage (10-30V)
- IP69K ingress protection
- Single flash meets R65 approval (amber)
- Manufactured with 3W amber LEDs
- Link multiple units for synchronised flash
- Low profile 11mm design
- Self-adhesive gasket for quick fit or screw fit

KEY POINTS



LED COLOURS



Part Number	3W LEDs	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
KLED3A	3	82 x 30 x 11mm	0.8A / 0.4A
KLED4A	4	90 x 30 x 11mm	1.0A / 0.5A
KLED6A	6	130 x 30 x 11mm	1.5A / 0.8A

HLED RANGE

MAIN FEATURES

- Multi-voltage (10-30V)
- IP69K ingress protection
- Single flash meets R65 approval (amber)
- Manufactured with 3W amber LEDs
- Link multiple units for sync / alternate flash
- Low profile 11mm design
- Vertically mounted 6 LED version (HLED6AV)

KEY POINTS



LED COLOURS



Part Number	3W LEDs	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
HLED3A	3	82 x 30 x 11mm	0.8A / 0.4A
HLED4A	4	98 x 30 x 11mm	1.0A / 0.5A
HLED6A	6	130 x 30 x 11mm	1.5A / 0.8A
HLED6AV	6	130 x 30 x 11mm	1.5A / 0.8A