



# LEDR65 RANGE

## MAIN FEATURES

- Multi-voltage (10-30V)
- 6 flash patterns
- Single, double & quad flash all R65 approved
- Link up to four units for sync / alternate flash
- Amber & blue models R65 approved
- Aluminium housing & polycarbonate lens

## KEY POINTS



## LED COLOURS



Part Number	3W LEDs	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
LED3R65A	3	89 x 34 x 22mm	0.4A / 0.2A
LED4R65A	4	117 x 34 x 22mm	0.6A / 0.3A
LED6R65A	6	155 x 34 x 22mm	0.9A / 0.5A

# GXLED RANGE

## MAIN FEATURES

- Multi-voltage (10-30V)
- 21 flash patterns
- Single, double, quad flash all R65 approved
- Manufactured with 3W LEDs
- Link multiple units for sync / alternate flash
- Available in 4 LED and 6 LED models
- Supplied with two mounting options
- Ideal for grille mounted applications

## KEY POINTS



## LED COLOURS



Part Number	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
GXLED4A	96 x 26 x 15mm	1.0A / 0.5A
GXLED6A	135 x 26 x 15mm	1.5A / 0.5A