



# TLED RANGE

## LED COLOURS



### MAIN FEATURES

- Multi-voltage (10-30V)
- Three flash patterns meet R65 approval
- Single, double and & quad all approved
- Manufactured with 3W LEDs
- Link multiple units for synchronised flash
- Low profile 7mm design
- Self-adhesive gasket for quick fit or screw fit



### KEY POINTS



Part Number	3W LEDs	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
TLED3A	3	82 x 31 x 7mm	0.5A / 0.2A
TLED4A	4	98 x 31 x 7mm	0.5A / 0.3A
TLED6A	6	131 x 31 x 7mm	0.6A / 0.3A

# VLED RANGE

## LED COLOURS



### MAIN FEATURES

- Multi-voltage (10-30V)
- Single, double & quad flash patterns meet R65 approval
- Manufactured with 5W LEDs
- Link multiple units for sync / alternate flash
- Low profile 9mm design
- Steady on function



### KEY POINTS



Part Number	5W LEDs	Dimensions (L) x (W) x (H)	Current @ 12V / 24V
VLED3A	3	76 x 29 x 9mm	1.3A / 0.6A
VLED4A	4	96 x 29 x 9mm	1.7A / 0.8A
VLED6A	6	120 x 29 x 9mm	2.5A / 1.3A