



SM3 & RM3 MODULE

MAIN FEATURES

- Multi-voltage (10-30V)
- SM3 (12 flash patterns), RM3 (16 flash patterns)
- Single flash meets R65 approval
- Manufactured with 3 x 3W amber LEDs
- Link multiple units for synchronised flash
- Current consumption: 0.5A @ 12V, 0.2A @ 24V
- Excellent additional warning light

LED COLOURS



SM3
Ø46.7 x 26mm (D)

RM3
Ø36 x 39mm (D)

KEY POINTS




Part Number	LED Colour	R65 Approved	Dimensions (Diam) x (H)
SM3A	Amber	-	46.7 x 26mm
SM3B	Blue	-	46.7 x 26mm
RM3A	Amber	✓	36 x 39mm
RM3B	Blue	✓	36 x 39mm

LAP9169X MODULE

MAIN FEATURES

- Multi-voltage (10-30V)
- 29 flash patterns
- Manufactured with 9 x 1W amber LEDs
- Link multiple units for synchronised flash
- Quick release connector
- Discreet design
- Excellent additional amber warning light

LED COLOURS



KEY POINTS



Part Number	Dimensions (Diameter) x (H)	Current @ 12V / 24V
LAP9169X	38 x 34mm	0.8A / 0.4A