



STRØLUX RANGE

MAIN FEATURES

- Multi-voltage (10-30V)
- Single & double LED row models available
- Manufactured with 5W OSRAM LEDs
- IP67 & IP69K ingress protection
- Strong polycarbonate lens
- Aluminium housing
- Combination of flood and spot reflectors



SLX1-10



SLX2-22



SLX1-31



SLX2-42

KEY POINTS



Style	Part Number	Length	5W Osram LEDs	Effective Lumen	Dimensions (mm)		Current (A)	
					Height	Depth	@12V	@24V
Single Row	SLX1-07	7" / 177mm	6	1283	40	54	2.1	1.1
	SLX1-10	10" / 246mm	9	2054	40	54	3.4	1.7
	SLX1-21	21" / 522mm	21	4652	40	54	8.0	3.9
	SLX1-31	31" / 798mm	33	7445	40	54	12.5	6.1
	SLX1-40	40" / 1005mm	42	9499	40	54	14.9	7.8
	SLX1-50	50" / 1281mm	54	12324	40	54	19.2	10.1
Double Row	SLX2-03	3" / 70mm	4	800	72	60	1.5	0.8
	SLX2-08	8" / 204mm	12	2100	70	67	3.8	2.0
	SLX2-14	14" / 357mm	24	4200	70	67	7.7	4.0
	SLX2-22	22" / 561mm	40	7000	70	67	14.6	7.2
	SLX2-32	32" / 815mm	60	10500	70	67	20.8	10.1
	SLX2-42	42" / 1076mm	80	14000	70	67	28.3	14.3
	SLX2-50	50" / 1274mm	96	16800	70	67	30.6	16.4