



STATIC RANGE



MAIN FEATURES

- EMC approved
- 70mph rated on magnetic version (LAP223 & LAP224)
- Supplied with 12V or 24V bulbs
- Amber model conforms to CAP168 regulations
- Single flash
- Nominal flash rate: 80 flashes per minute
- Current consumption: 1.0A @ 12V, 0.5A @ 24V
- -30°C to +50°C extreme temperature reliability

12V AMBER LENS MODELS

Part Number	Fitting	Weight	Dimensions (mm)
LAP223	Magnetic	1.1KG	Ø153 x 177 (H)
LAP221	3-Point	0.8KG	Ø153 x 177 (H)
LAP225	Single Point	0.8KG	Ø130 x 186 (H)

24V AMBER LENS MODELS

Part Number	Fitting	Weight	Dimensions (mm)
LAP224	Magnetic	1.1KG	Ø153 x 177 (H)
LAP222	3-Point	0.8KG	Ø153 x 177 (H)
LAP226	Single Point	0.8KG	Ø130 x 186 (H)

A-ELPB-2 RANGE



MAIN FEATURES

- Multi-voltage (10-30V)
- Single flash meets CAP168 & ICAO airport requirements
- Manufactured with 24 x 1W LEDs
- 70mph rated on magnetic version (A-ELPB020-2)
- Current consumption: 1.6A @ 12V, 0.8A @ 24V
- -30°C to +50°C extreme temperature reliability

Part Number	Fitting	Weight	Dimensions (mm)	Current Consumption
A-ELPB020-2	Magnetic	0.6KG	Ø141 x 115 (H)	1.6A / 0.8A
A-ELPB050-2	3-Point	0.4KG	Ø141 x 101 (H)	1.6A / 0.8A
A-ELPB060-2	Single Point	0.4KG	Ø116 x 101 (H)	1.6A / 0.8A

LOW PROFILE AIRPORT BEACONS

Check out page 13 for our low profile range of airport beacons.

